

[M-00 FRONT]



[M-00 BACK]



Nickname: “Moo.” (“Mr. Moo,” to some). Tipping the scales at roughly the same weight as a blue-ribbon Holstein, and built beefier than a ’56 Buick Roadstar, our M-00 stands alone in any field. And that’s just the part you can see. Under the hood you’ll find a real 75-watt amplifier and audiophile grade mini monitor that combine to produce a laughably versatile studio tool engineered to help you respond to every single important sonic decision with a quick and easy, “duh?”



[SPECIFICATIONS]

System Type:	Integrated, self-powered near/mid-field monitor
Configuration:	2-way acoustic suspension
Woofers:	4.5" treated paper
Tweeter:	1" soft fabric dome
Magnetic Shielding:	Full
Amplifier Power:	75W (continuous rms/ch), 150W (100ms peak)
Peak Acoustic Output @1M:	11dB SPL (100ms pink noise @ 1M)
Residual Hum/Noise:	< 20dB SPL (A-weighted @ 1M)
THD @ 90dB SPL:	< 1.0% (100Hz - 10KHz @ 1M)
Response \pm 2dB (1/3 oct. swept noise):	98Hz - 20KHz @ 1M, 93 Hz - 20KHz @ 2M
-6dB LF Cutoff:	80Hz (in-room response)
Dimensions/Weight:	9"h x 5.7"w x 7.3"d/14 lbs
Monitor Enclosure Materials:	Cast aluminum/zinc alloy body, Glass-filled ABS baffle
Input Connectors:	XLR, TRS, RCA
Controls:	
Input sensitivity:	-10, +4db
Listening proximity:	-10, +4db
Power:	On, Auto-On, Off

