

[iC2]



The iC2 features NHT's (U.S. Patent #5,952,619) 3-tweeter array that produces flat frequency response up to 60 degrees off-axis that creates a consistent soundfield throughout any room. Sort of a blanket of sound, really. Well, come to think of it, more like a very thick, massively large, fluffy down comforter of sound hung carefully from the ceiling as opposed to let's say, a thin, cotton sheet taped to a light fixture. See the difference? Probably not. But you will hear it



[SPECIFICATIONS]

System type:	2-way in-ceiling loudspeaker
Woofers:	6.5" long-throw polypropylene cone
Tweeter:	3 x 1" fluid cooled soft dome (NHT U.S. Patent #5,952,619)
Crossover:	2.2kHz, 18dB/octave high-pass, 6dB/octave low pass
Response:	60Hz - 20kHz, +/- 3dB
Sensitivity:	86dB (2.83v@1m)
Impedance:	8 ohms nominal
Recommended Amplifier Power:	10W/ch minimum, 100W/ch maximum
Inputs:	2 each professional grade, gold plated spring posts
Weight:	5 lbs
Cutout Dimensions:	8 13/16" dia.
Bezel Dimensions:	9 11/16" dia.
Depth Behind Wall:	4 13/16"
Finish:	Matte white (paintable)

