

[ iC3 ]



Our iC3, not unlike our iC2, utilizes an all aluminum 6.5" long-throw woofer and (U.S. Patent #5,952,619) 3-tweeter array. And while this configuration gives you the same killer dispersion and even frequency response as the iC2, the difference is we've super-sized the iC3's power handling. This super-sizing provides higher output; improved detail and lower distortion, which make the iC3, sound absolutely lights out as home theater surround channels and in other life-critical listening installations.



## [ SPECIFICATIONS ]

System type:	2-way in-ceiling loudspeaker
Woofers:	6.5" long-throw polypropylene cone
Tweeter:	3 x 1" fluid cooled aluminum dome (NHT U.S. Patent #5,952,619)
Crossover:	1.9kHz, 18dB/octave high-pass, 12dB/octave low pass
Response:	50Hz - 20kHz, +/- 3dB
Sensitivity:	85dB (2.83V@1m)
Impedance:	8 ohms nominal
Recommended Amplifier Power:	10W/ch minimum, 125W/ch maximum
Inputs:	2 each professional grade, gold plated spring posts
Weight:	5 lbs
Cutout Dimensions:	8 13/16" dia.
Bezel Dimensions:	9 11/16" dia.
Depth Behind Wall:	4 13/16"
Finish:	Matte white (paintable)

