

[ iW2 ]



Yikes. Talk about spreading a good thing around. Okay, let's. This is what puts our 3-way, iW2 into a league of one -- dispersion, both even and lots of it -- which isn't normally a trait ever even muttered with in-walls. But then, the iW2 is not your average bear. The iW2 features a 3-way "flying bridge" design loaded with two soft-dome 1.25" midrange drivers, plus a soft-dome 3/4" tweeter that hovers over the real deal 6.5" long-throw polypropylene woofer, all of which takes us back to where we started -- Yikes.



## [ SPECIFICATIONS ]

System type:	3-way in-wall loudspeaker
Woofers:	6.5" long-throw polypropylene cone
Midrange:	2 x 1.25" fluid cooled soft dome
Tweeter:	.75" fluid cooled soft dome
Crossover:	4kHz and 1.75Hz, 12dB/octave high-pass, 12dB/octave band pass, 12dB/octave low pass
Response:	62Hz - 20kHz, +/- 3dB
Sensitivity:	86dB (2.83V@1m)
Impedance:	8 ohms nominal
Recommended Amplifier Power:	10W/ch minimum, 125W/ch maximum
Inputs:	2 each professional grade, gold plated spring posts
Weight:	7 lbs
Cutout Dimensions:	10 1/4" H 8 1/8" W
Bezel Dimensions:	11 3/8" H 9 1/4" W
Depth Behind Wall:	3 1/4"
Finish:	Matte white (paintable)

